

CEON LUBEN FS 312



Trunk piston engine oil for medium speed diesel engines operating on distillate fuel, Very Low Sulphur Fuel (VLSFO) <0.5% Sulphur Content and Ultra Low Sulphur Fuel (ULSFO) <0.1% Sulphur Content.

PRODUCT DESCRIPTION

LUBEN FS series are trunk piston engine oil designed for use in medium speed diesel engines operating on distillate fuels and Very Low Sulphur Fuels (VLSFO) having sulphur contents <0.5 %. The modern additive technology used in this oil provides superior engine cleanliness & protection. This oil is available in SAE 30 & SAE 40 viscosity grades with a BN (Base Number) 12 KOH/g. These oils exhibit a high degree of water tolerance and meet the performance requirements of API CF.

FEATURES & BENEFITS

- Superior detergency ensures piston and crankcase cleanliness.
- Improved anti-wear property minimises engine wear and reduces maintenance costs.
- Excellent thermo-oxidative stability retards oil degradation and controls its viscosity.
- Reserve BN ensures protection of engine parts against corrosive combustion products.
- Better demulsibility characteristics ensure water separation leading to trouble free operation.
- Special rust & corrosion inhibitors prevent corrosion of engine parts in severe salt water environment.

APPLICATIONS

- Recommended for medium speed engines used in marine, power generation and industrial applications operating on distillate fuel, Very Low Sulphur Fuel (VLSFO) having sulphur contents <0.5% and Ultra Low Sulphur Fuel (ULSFO) having Sulphur content less than 0.1%. This product is also suitable for older engines where liner-lacquer is not a potential problem.
- Oils of appropriate BN to be chosen based on the sulphur content of fuel used. Follow manufacturers' recommendation for selection of suitable BN level/ viscosity grade.
- Also recommended for general lubrication of shipboard equipment where specialised lubricants are not required or use of API CF quality oils are adequate.

TYPICAL PROPERTIES

LUBEN FS SERIES		312	412	315	415	320	420
Test Parameters	ASTM Method	Typical Values					
Viscosity @ 100°C, cSt	D 445	10.9	14.5	11.1	14.3	11.1	14.5
Viscosity Index	D 2270	99	98	99	98	100	98
Flash Point, °C	D 92	>215	>215	>215	>215	>215	>215
Pour Point, °C	D 97	-18	-18	-18	-18	-18	-18
BN, mg KOH/g	D 2896	12	12	15	15	20	20
Density @ 15 °C, kg/l	D 1298	0.889	0.896	0.891	0.897	0.894	0.900